

**Description**

Fastener Length: 15/16", roughly 360 pieces per pound, MS20426 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20426AD615
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-582-1295
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



## P/N MS20426AD6-15 Specifications

<b>Fastener Length:</b>	0.928 Inches Minimum And 0.948 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.187 Inches Minimum And 0.191 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.353 Inches Nominal
<b>Grip Length:</b>	0.647 Nominal Mils And 0.667 Nominal Centimeters
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 1100 Overall Or Aluminum Alloy 6061 Overall Or Aluminum Alloy 2017 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 5056 Overall
<b>Material Document And Classification:</b>	Mil-t-5674,f Mil Spec 1st Material Response Overall Or Qq-a-430,h13 Fed Spec 2nd Material Response Overall Or Qq-a-430,t4 Fed Spec 3rd Material Response Overall Or Qq-a-430,t4 Fed Spec 4th Material Response Overall Or Qq-a-430,h32 Fed Spec 5th Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD6-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.