

Description

Fastener Length: 15/16", roughly 360 pieces per pound, MS20426 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426AD615
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-582-1295
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20426AD6-15 Specifications

Fastener Length:	0.928 Inches Minimum And 0.948 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.187 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.353 Inches Nominal
Grip Length:	0.647 Nominal Mils And 0.667 Nominal Centimeters
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 1100 Overall Or Aluminum Alloy 6061 Overall Or Aluminum Alloy 2017 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 5056 Overall
Material Document And Classification:	Mil-t-5674,f Mil Spec 1st Material Response Overall Or Qq-a-430,h13 Fed Spec 2nd Material Response Overall Or Qq-a-430,t4 Fed Spec 3rd Material Response Overall Or Qq-a-430,t4 Fed Spec 4th Material Response Overall Or Qq-a-430,h32 Fed Spec 5th Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD6-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.