

**Description**

MS20426AD8-14 Solid Rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20426AD814
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-233-4782
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N MS20426AD8-14 Specifications

<b>Fastener Length:</b>	0.865 Inches Minimum And 0.885 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.249 Inches Minimum And 0.253 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.472 Inches Minimum And 0.480 Inches Maximum
<b>Grip Length:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Shear Strength:</b>	26000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Oxide Film Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD8-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.