

Description

MS20426AD8-14 Solid Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20426AD814 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-233-4782 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20426AD8-14 Specifications

| | |
|---|--|
| Fastener Length: | 0.865 Inches Minimum And 0.885 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.249 Inches Minimum And 0.253 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.472 Inches Minimum And 0.480 Inches Maximum |
| Grip Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Shear Strength: | 26000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD8-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.