

P/N MS20426AD8-4

Description

length: 1/4", diameter: 1/4", countersunk precision head, aluminum alloy, roughly 560 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS20426AD84

Minimum Qty (MOQ): 1 Pound

NSN: 5320-01-365-4938

EAR99 ECCN:

National Motor Freight: 013630, Alum Rivets









^{*} See page 2 for technical characteristics

P/N MS20426AD8-4 Specifications

Fastener Length:	0.2400 Inches Minimum And 0.2600 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.249 Inches Minimum And 0.253 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.472 Inches Minimum And 0.480 Inches Maximum
Countersink Angle:	99.5 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541,cl 1a Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20426AD8-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.