

Description

Fastener Length: 2-1/2

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20426AD840
Minimum Qty (MOQ):	1
NSN:	5320-00-117-6908
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N MS20426AD8-40 Specifications

Fastener Length:	2.490 Inches Minimum And 2.510 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.249 Inches Minimum And 0.253 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.472 Inches Minimum And 0.480 Inches Maximum
Grip Length:	2.115 Nominal Mils And 2.135 Nominal Centimeters
Shear Strength:	26000 Single Pounds Per Square Inch
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426AD8-40> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.