

## Description

length: 1/4", diameter: 3/32", countersunk precision head, aluminum alloy, roughly 4900 pieces per pound, Military Standard MIL-R-5674, MS20426 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS20426B34          |
| Minimum Qty (MOQ):      | 1 Pound             |
| NSN:                    | 5320-00-119-6809    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

## P/N MS20426B3-4 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.240 Inches Minimum And 0.260 Inches Maximum  |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)                           |
| <b>Shank Diameter:</b>                                | 0.093 Inches Minimum And 0.097 Inches Maximum  |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip  |
| <b>Head Major Diameter:</b>                           | 0.175 Inches Minimum And 0.183 Inches Maximum  |
| <b>Grip Length:</b>                                   | 0.099 Nominal Mils And 0.119 Nominal Centimeters   |
| <b>Shear Strength:</b>                                | 24000 Single Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                             | 99.5 Degrees Minimum And 100.5 Degrees Maximum   |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Overall  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Overall   |
| <b>Surface Treatment:</b>                             | Anodize Overall Or Oxide Film Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426B3-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.