

**Description**

Fastener Length: 1/4, roughly 4511 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS20426B3-4.5](#)

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS20426B345         |
| Minimum Qty (MOQ):      | 1000                |
| NSN:                    | 5320-00-508-8438    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

## P/N MS20426B3-4-5 Specifications

|                             |  |
|-----------------------------|--|
| <b>Fastener Length:</b>     | 0.271 Inches Minimum And 0.291 Inches Maximum                                  |
| <b>Head Style:</b>          | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>      | 0.093 Inches Minimum And 0.097 Inches Maximum                                  |
| <b>Shank Style:</b>         | Straight W/radius Chamfered Tip  |
| <b>Head Major Diameter:</b> | 0.175 Inches Minimum And 0.183 Inches Maximum                                  |
| <b>Grip Length:</b>         | 0.150 Nominal Centimeters  |
| <b>Shear Strength:</b>      | 24000 Single Pounds Per Square Inch  |
| <b>Countersink Angle:</b>   | 99.5 Degrees Minimum And 100.5 Degrees Maximum                                 |
| <b>Heat Treatment:</b>      | H-32 Strain Hardened Overall   |
| <b>Material:</b>            | Aluminum Alloy 5056 Overall  |
| <b>Surface Treatment:</b>   | Anodize Overall  |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426B3-4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.