

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS20426B45A |
| Minimum Qty (MOQ): | 1000 EA |
| NSN: | 5320-01-359-6974 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20426B4-5A Specifications

| | |
|-----------------------------|--|
| Fastener Length: | 0.3025 Inches Minimum And 0.3225 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.1240 Inches Minimum And 0.1280 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.2210 Inches Minimum And 0.2290 Inches Maximum |
| Countersink Angle: | 99.5 Degrees Minimum And 101.5 Degrees Maximum |
| Material: | Aluminum Alloy 5056 Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426B4-5A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.