

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20426B45A
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-359-6974
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20426B4-5A Specifications

Fastener Length:	0.3025 Inches Minimum And 0.3225 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.1240 Inches Minimum And 0.1280 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.2210 Inches Minimum And 0.2290 Inches Maximum
Countersink Angle:	99.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Aluminum Alloy 5056 Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426B4-5A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.