

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20426B511 |
| Minimum Qty (MOQ): | 255 EA |
| NSN: | 5320-01-069-8950 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS20426B5-11 Specifications

| | |
|---|--|
| Fastener Length: | 0.678 Inches Minimum And 0.698 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.155 Inches Minimum And 0.159 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.290 Inches Maximum |
| Shear Strength: | 24000 Single Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Heat Treatment: | H-32 Strain Hardened Overall |
| Material: | Aluminum Alloy 5056 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426B5-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.