

Description

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426B611
Minimum Qty (MOQ):	505 EA
NSN:	5320-01-218-3260
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N MS20426B6-11 Specifications

<b>Fastener Length:</b>	0.646 Inches Minimum And 0.666 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.349 Inches Minimum And 0.357 Inches Maximum
<b>Shear Strength:</b>	24000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Heat Treatment:</b>	H-32 Strain Hardened Overall
<b>Material:</b>	Aluminum Alloy 5056 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426B6-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.