

Description

Fastener Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20426D310 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-117-6399 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS20426D3-10 Specifications

| | |
|---|--|
| Fastener Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.093 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.175 Inches Minimum And 0.183 Inches Maximum |
| Grip Length: | 0.474 Nominal Mils And 0.494 Nominal Centimeters |
| Shear Strength: | 33000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Material: | Aluminum Alloy 2017 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426D3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.