

**Description**

Fastener Length: 1/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20426D53
Minimum Qty (MOQ):	100
NSN:	5320-01-613-1823
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N MS20426D5-3 Specifications

<b>Fastener Length:</b>	0.1325 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Head Height:</b>	0.055 Inches Nominal
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.282 Inches Minimum And 0.290 Inches Maximum
<b>End Item Identification:</b>	5310-01-024-6299
<b>Countersink Angle:</b>	99.50 Degrees Minimum And 100.50 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Rivet, Solid, Countersunk 100 Degrees, Precision Head
<b>Special Features:</b>	Rivet Has A Raised Teat On Head. Teat Has A Max Dia Of 0.030 Inches. Overall Length Of Rivet Is 0.1775 To 0.1975 Inches. Color Is Gold/yellow.
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2017 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541, Class 1a, Gold/yellow Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426D5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.