

**Description**

length: 5/16", diameter: 5/32", countersunk precision head, 2017-t4 aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS20426D55          |
| Minimum Qty (MOQ):      | 100                 |
| NSN:                    | 5320-00-685-5934    |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

## P/N MS20426D5-5 Specifications

|  |   |
|--|---|
| <b>Fastener Length:</b>                      | 0.312 Inches Nominal  |
| <b>Head Style:</b>                           | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)  |
| <b>Head Height:</b>                          | 0.055 Inches Nominal  |
| <b>Shank Diameter:</b>                       | 0.156 Inches Nominal  |
| <b>Shank Style:</b>                          | Straight W/radius Chamfered Tip   |
| <b>Head Major Diameter:</b>                  | 0.286 Inches Nominal  |
| <b>Countersink Angle:</b>                    | 100.0 Degrees Nominal   |
| <b>Material:</b>                             | Aluminum Alloy 1100 Overall Or Aluminum Alloy 2017 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 2117 Overall Or Aluminum Alloy 5056 Overall |
| <b>Material Document And Classification:</b> | II-w-7986 Mil Spec 10th Material Response Overall   |
| <b>Surface Treatment:</b>                    | Anodize Overall   |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426D5-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.