

Description

length: 5/8", diameter: 3/16", countersunk precision head, 2017-t4 aluminum alloy, roughly 520 pieces per pound, MS20426 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426D610
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-117-6409
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20426D6-10 Specifications

Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Grip Length:	0.334 Nominal Mils And 0.354 Nominal Centimeters
Shear Strength:	33000 Single Pounds Per Square Inch
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 2017 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426D6-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.