

**Description**

Fastener Length: 1-1/4

\* Manufacturer certifications are shipped with your order FREE of charge

[Order this part online](#)**Additional Information**

SKU / Model:	MS20426D620
Minimum Qty (MOQ):	100
NSN:	5320-00-117-6414
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N MS20426D6-20 Specifications

<b>Identification Code Color:</b>	Yellow
<b>Fastener Length:</b>	1.240 Inches Minimum And 1.260 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Head Height:</b>	0.070 Inches Nominal
<b>Shank Diameter:</b>	0.187 Inches Minimum And 0.191 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.349 Inches Minimum And 0.357 Inches Maximum
<b>Grip Length:</b>	0.865 Nominal Mils And 0.885 Nominal Centimeters
<b>Shear Strength:</b>	33000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2017 Overall
<b>Material Document And Classification:</b>	Qq-a-430,t4,uns A92017 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Oxide Film Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541,class 1a Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	96906-ms20426 Government Standard And 88044-an426/canceled/ Government Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426D6-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.