

Description

Fastener Length: 1-3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20426D622
Minimum Qty (MOQ):	100
NSN:	5320-01-295-4068
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20426D6-22 Specifications

Identification Code Color:	Yellow
Fastener Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.357 Inches Maximum
Shear Strength:	33000 Single Pounds Per Square Inch
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Special Features:	Raised Teat,identification Mark On Head
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2017 Overall
Material Document And Classification:	Qq-a-430,t4 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541,cl 1a Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426D6-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.