

**Description**

Fastener Length: 1-3/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS20426D622         |
| Minimum Qty (MOQ):      | 100                 |
| NSN:                    | 5320-01-295-4068    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

## P/N MS20426D6-22 Specifications

|   |  |
|---|--|
| <b>Identification Code Color:</b>                     | Yellow   |
| <b>Fastener Length:</b>                               | 1.365 Inches Minimum And 1.385 Inches Maximum                                  |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                                | 0.186 Inches Minimum And 0.190 Inches Maximum                                  |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip  |
| <b>Head Major Diameter:</b>                           | 0.357 Inches Maximum   |
| <b>Shear Strength:</b>                                | 33000 Single Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                             | 99.5 Degrees Minimum And 100.5 Degrees Maximum                                 |
| <b>Special Features:</b>                              | Raised Teat,identification Mark On Head  |
| <b>Heat Treatment:</b>                                | T-4 Solution Heat Treated Overall  |
| <b>Material:</b>                                      | Aluminum Alloy 2017 Overall  |
| <b>Material Document And Classification:</b>          | Qq-a-430,t4 Fed Spec Single Material Response Overall                          |
| <b>Surface Treatment:</b>                             | Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-5541,cl 1a Mil Spec Single Treatment Response Overall                    |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426D6-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.