

Description

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS20426D88          |
| Minimum Qty (MOQ):      | 200 EA              |
| NSN:                    | 5320-00-117-6422    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

## P/N MS20426D8-8 Specifications

|                                                       |                                                                                                          |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| <b>Fastener Length:</b>                               | 0.490 Inches Minimum And 0.510 Inches Maximum                                                            |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)                           |
| <b>Shank Diameter:</b>                                | 0.249 Inches Minimum And 0.253 Inches Maximum                                                            |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip                                                                          |
| <b>Head Major Diameter:</b>                           | 0.472 Inches Minimum And 0.480 Inches Maximum                                                            |
| <b>Grip Length:</b>                                   | 0.115 Nominal Mils And 0.135 Nominal Centimeters                                                         |
| <b>Shear Strength:</b>                                | 33000 Single Pounds Per Square Inch                                                                      |
| <b>Countersink Angle:</b>                             | 99.5 Degrees Minimum And 100.5 Degrees Maximum                                                           |
| <b>Material:</b>                                      | Aluminum Alloy 2017 Overall                                                                              |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Overall                                                       |
| <b>Surface Treatment:</b>                             | Anodize Overall Or Oxide Film Overall                                                                    |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426D8-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.