



MILITARY ★ FASTENERS

Military-Fasteners.com

P/N MS20426DD4-28A

Description

Fastener Length: 1-3/4", roughly 450 pieces per pound, MS20426 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426DD428A
Minimum Qty (MOQ):	250
NSN:	5320-00-165-8799
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20426DD4-28A Specifications

Identification Code Color:	Natural
Fastener Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Head Height:	0.042 Inches Nominal
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Grip Length:	1.552 Nominal Mils And 1.572 Nominal Centimeters
Shear Strength:	41000 Single Pounds Per Square Inch
Countersink Angle:	99.5 Degrees Minimum And 101.5 Degrees Maximum
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy 7050 Overall
Material Document And Classification:	Qq-a-430,t73 Uns A97050 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 1 Mil Spec Single Treatment Response Overall
Specification/standard Data:	96906-ms20426 Government Standard And 88044-an426/canceled/ Government Standard
Nondefinitive Spec/std Data:	2024 Composition And T4 Condition

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426DD4-28A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.