

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426DD68D
Minimum Qty (MOQ):	100 EA
NSN:	5320-01-604-6092



* See page 2 for technical characteristics

P/N MS20426DD6-8D Specifications

Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Straight With Tapered Tip
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Chamfer Length:	0.047 Inches Nominal
Tip Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
End Item Identification:	C130k
Grip Length:	0.070 Inches Nominal
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Part Name Assigned By Controlling Agency:	Rivet,solid,cuntersunk 100 Degree Pricision Head,aluminum And Titanium Columbium Alloy
Special Features:	Material:2024-t4 Al Alloy
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Ms20426 Mil Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 1,dichromate Seal Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426DD6-8D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.