

Description

length: 5/16", diameter: 5/32", countersunk precision head, 2219-t81 aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426E55
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-220-8780
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20426E5-5 Specifications

Fastener Length:	0.312 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.290 Inches Maximum
Shear Strength:	41000 Single Pounds Per Square Inch
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-430,comp 7050 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541,cl 1a Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426E5-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.