

**Description**

length: 7/16", diameter: 5/32", countersunk precision head, 2219-t81 aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20426E57
Minimum Qty (MOQ):	100
NSN:	5320-01-288-5666
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N MS20426E5-7 Specifications

<b>Fastener Length:</b>	0.428 Inches Minimum And 0.448 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.290 Inches Maximum
<b>Shear Strength:</b>	41000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Special Features:</b>	Aluminum Alloy 7050
<b>Heat Treatment:</b>	T-73 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541,class 1a Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426E5-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.