

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20426T64
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-475-8647
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS20426T6-4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Countersink Angle:	95.0 Degrees Minimum And 100.5 Degrees Maximum
Part Name Assigned By Controlling Agency:	Rivet, Solid, Countersunk 100 Degrees, Precision Head
Special Features:	The Conical Surface Of The Head Shall Be Concentric With The Shank Of The Rivet Within .005;head-cocking Angle Relative To Axis Of Rivet 1/2 Degree Max;rivets May Be Furnished Within Plain Ends, Or Chamfered Ends Witha A Radius To The "t" Dimentions Or A 20 Degree Chamfer To The "s" Dimention
Material:	Titanium Alloy Uns R58450 Overall
Material Document And Classification:	Ams4982 Assn Std Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426T6-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.