

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20426T64
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-475-8647
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N MS20426T6-4 Specifications

<b>Fastener Length:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.349 Inches Minimum And 0.357 Inches Maximum
<b>Countersink Angle:</b>	95.0 Degrees Minimum And 100.5 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Rivet, Solid, Countersunk 100 Degrees, Precision Head
<b>Special Features:</b>	The Conical Surface Of The Head Shall Be Concentric With The Shank Of The Rivet Within .005;head-cocking Angle Relative To Axis Of Rivet 1/2 Degree Max;rivets May Be Furnished Within Plain Ends, Or Chamfered Ends Witha A Radius To The "t" Dimentions Or A 20 Degree Chamfer To The "s" Dimention
<b>Material:</b>	Titanium Alloy Uns R58450 Overall
<b>Material Document And Classification:</b>	Ams4982 Assn Std Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426T6-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.