

**Description**

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS20426T65                                |
| Minimum Qty (MOQ):      | 30 EA                                     |
| NSN:                    | 5320-01-435-6439                          |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



\* See page 2 for technical characteristics

## P/N MS20426T6-5 Specifications

|   |  |
|---|--|
| <b>Identification Code Color:</b>                     | Yellow   |
| <b>Fastener Length:</b>                               | 0.313 Inches Nominal   |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                                | 0.188 Inches Nominal   |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip  |
| <b>Head Major Diameter:</b>                           | 0.357 Inches Maximum   |
| <b>Countersink Angle:</b>                             | 99.5 Degrees Minimum And 100.5 Degrees Maximum                                 |
| <b>Material:</b>                                      | Titanium Alloy Uns R58450 Overall  |
| <b>Material Document And Classification:</b>          | Ams4982 Assn Std Single Material Response Overall                              |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-5541 Class 1a Gold/yellow Mil Spec Single Treatment Response Overall     |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426T6-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.