

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | MS20426T67 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-214-5979 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



* See page 2 for technical characteristics

P/N MS20426T6-7 Specifications

| | |
|--|--|
| Fastener Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.186 Inches Minimum And 0.190 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.357 Inches Maximum |
| Shear Strength: | 50000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Heat Treatment: | Annealed Overall |
| Material: | Titanium Alloy Uns R58450 Overall |
| Material Document And Classification: | Ams 4982 Assn Std Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20426T6-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.