

Description

Fastener Length: 1/4", roughly 5600 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS204272C3 |
| Minimum Qty (MOQ): | 1000 |
| NSN: | 5320-00-233-4835 |
| Schedule B: | 7318.23.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N MS20427-2C3 Specifications

| | |
|---|---|
| Fastener Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.061 Inches Minimum And 0.065 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.090 Inches Minimum And 0.135 Inches Maximum |
| Shear Strength: | 32000 Single Pounds Per Square Inch |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Heat Treatment: | Annealed Overall |
| Material: | Steel Comp 1010 Overall Or Steel Comp 1011 Overall Or Steel Comp 1012 Overall Or Steel Comp 1013 Overall Or Steel Comp 1015 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427-2C3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.