



★ FASTENERS

Military-Fasteners.com

P/N MS20427-4C7

Description

Fastener Length: 1/2", roughly 590 pieces per pound, MS20427 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS204274C7
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-208-9632
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS20427-4C7 Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.201 Inches Minimum And 0.236 Inches Maximum
Shear Strength:	32000 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Heat Treatment:	Annealed Overall
Material:	Steel Comp 1010 Overall Or Steel Comp 1011 Overall Or Steel Comp 1012 Overall Or Steel Comp 1013 Overall Or Steel Comp 1015 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427-4C7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.