

Description

Fastener Length: 1"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS204275C16
Minimum Qty (MOQ):	65 EA
NSN:	5320-00-843-0534
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20427-5C16 Specifications

Fastener Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.256 Inches Minimum And 0.297 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Heat Treatment:	Annealed Overall
Material:	Steel Comp 1010 Overall Or Steel Comp 1011 Overall Or Steel Comp 1012 Overall Or Steel Comp 1013 Overall Or Steel Comp 1015 Overall
Material Document And Classification:	Fed Std 66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427-5C16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.