

**Description**

Fastener Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS20427F311                                 |
| Minimum Qty (MOQ):      | 255 EA                                      |
| NSN:                    | 5320-01-437-9582                            |
| Schedule B:             | 7318.23.0000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20427F3-11 Specifications

|                             |  |
|-----------------------------|--|
| <b>Fastener Length:</b>     | 0.6775 Inches Minimum And 0.6975 Inches Maximum                                |
| <b>Head Style:</b>          | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>      | 0.093 Inches Minimum And 0.097 Inches Maximum                                  |
| <b>Shank Style:</b>         | Straight   |
| <b>Head Major Diameter:</b> | 0.155 Inches Minimum And 0.190 Inches Maximum                                  |
| <b>Shear Strength:</b>      | 6500 Single Pounds Per Square Inch   |
| <b>Countersink Angle:</b>   | 98.5 Degrees Minimum And 101.5 Degrees Maximum                                 |
| <b>Heat Treatment:</b>      | Annealed Overall   |
| <b>Material:</b>            | Steel Comp 302 Overall Or Steel Comp 304 Overall                               |

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427F3-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.