

Description

Fastener Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS20427F316 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5320-00-935-9061 |
| Schedule B: | 7318.16.0060 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20427F3-16 Specifications

| | |
|--|--|
| Fastener Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.093 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.155 Inches Minimum And 0.190 Inches Maximum |
| Shear Strength: | 65000 Single Pounds Per Square Inch |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Heat Treatment: | Annealed Overall |
| Material: | Steel Comp 302 Overall Or Steel Comp 304 Overall |
| Material Document And Classification: | Qq-w-423 Comp 302 Fed Spec 1st Material Response Overall Or Qq-w-423 Comp 304 Fed Spec 2nd Material Response Overall |

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427F3-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.