

## Description

length: 1/2", diameter: 3/32", 100° countersunk head, corrosion resistant steel, roughly 905 pieces per pound, MS20427 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS20427F38
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-118-1970
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS20427F3-8 Specifications

<b>Fastener Length:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.155 Inches Minimum And 0.190 Inches Maximum
<b>Grip Length:</b>	0.360 Inches Nominal
<b>Shear Strength:</b>	65000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Steel Comp 302 Overall Or Steel Comp 304 Overall
<b>Material Document And Classification:</b>	Qq-w-423,cond A Fed Spec All Material Responses Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427F3-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.