

Description

Fastener Length: 7/8", roughly 295 pieces per pound, MS20427 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20427F414
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-291-0126
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS20427F4-14 Specifications

Fastener Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.201 Inches Minimum And 0.236 Inches Maximum
Grip Length:	0.688 Inches Nominal
Shear Strength:	65000 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Heat Treatment:	Annealed Overall
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall
Material Document And Classification:	Qq-w-423,cond A Fed Spec All Material Responses Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427F4-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.