



★ FASTENERS

Military-Fasteners.com

P/N MS20427F4-14

Description

Fastener Length: 7/8", roughly 295 pieces per pound, MS20427 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS20427F414 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-291-0126 |
| Schedule B: | 7318.23.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N MS20427F4-14 Specifications

| | |
|--|--|
| Fastener Length: | 0.865 Inches Minimum And 0.885 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.201 Inches Minimum And 0.236 Inches Maximum |
| Grip Length: | 0.688 Inches Nominal |
| Shear Strength: | 65000 Single Pounds Per Square Inch |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Heat Treatment: | Annealed Overall |
| Material: | Steel Comp 302 Overall Or Steel Comp 304 Overall |
| Material Document And Classification: | Qq-w-423,cond A Fed Spec All Material Responses Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427F4-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.