

**Description**

Fastener Length: 35/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20427F49
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-526-2958
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20427F4-9 Specifications

<b>Fastener Length:</b>	0.552 Inches Minimum And 0.572 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.201 Inches Minimum And 0.236 Inches Maximum
<b>Shear Strength:</b>	65000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	66,300 Series Fed Std Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427F4-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.