

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20427F512
Minimum Qty (MOQ):	95 EA
NSN:	5320-00-764-3743
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N MS20427F5-12 Specifications

Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.257 Inches Minimum And 0.298 Inches Maximum
Grip Length:	0.516 Inches Nominal
Shear Strength:	65000 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Heat Treatment:	Annealed Overall
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall
Material Document And Classification:	Qq-w-423,cond A Fed Spec All Material Responses Overall

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427F5-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.