

**Description**

Fastener Length: 1-1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20427F520
Minimum Qty (MOQ):	80 EA
NSN:	5320-00-732-0315
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N MS20427F5-20 Specifications

<b>Fastener Length:</b>	1.240 Inches Minimum And 1.260 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.256 Inches Minimum And 0.297 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	66,300 Series Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427F5-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.