

Description

Fastener Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20427F67
Minimum Qty (MOQ):	130 EA
NSN:	5320-00-550-4738
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20427F6-7 Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.323 Inches Minimum And 0.365 Inches Maximum
Grip Length:	0.157 Inches Nominal
Shear Strength:	65000 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Heat Treatment:	Annealed Overall
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall
Material Document And Classification:	Qq-w-423,cond A Fed Spec All Material Responses Overall

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427F6-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.