

Description

Fastener Length: 5/8, roughly 650 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20427M310
Minimum Qty (MOQ):	200
NSN:	5320-00-637-1432
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



P/N MS20427M3-10 Specifications

Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.155 Inches Minimum And 0.190 Inches Maximum
Grip Length:	0.485 Inches Nominal
Shear Strength:	49000 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy 400 Overall Or Nickel Alloy R-405 Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.