

Description

Fastener Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------------------|
| SKU / Model: | MS20427M311 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-006-5035 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N MS20427M3-11 Specifications

| | |
|----------------------------------------------|--------------------------------------------------------------------------------|
| Fastener Length: | 0.677 Inches Minimum And 0.697 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.093 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.155 Inches Minimum And 0.190 Inches Maximum |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Heat Treatment: | Annealed Overall |
| Material: | Nickel Alloy 400 Overall Or Nickel Alloy R-405 Overall |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M3-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.