

**Description**

Fastener Length: 1-1/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20427M318
Minimum Qty (MOQ):	35 EA
NSN:	5320-01-490-6234



NO IMAGE  
AVAILABLE

## P/N MS20427M3-18 Specifications

<b>Fastener Length:</b>	1.115 Inches Minimum And 1.135 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.1548 Inches Minimum And 0.1900 Inches Maximum
<b>End Item Identification:</b>	F-22
<b>Grip Length:</b>	0.985 Inches Nominal
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Rivet
<b>Special Features:</b>	Shear Strength 49,000 Psi To 59,000 Psi
<b>Material:</b>	Nickel Alloy R-405 Overall Or Nickel Alloy 400 Overall
<b>Material Document And Classification:</b>	Qq-n-281 Annealed Fed Spec Single Material Response Overall

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M3-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.