

Description

Fastener Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20427M318
Minimum Qty (MOQ):	35 EA
NSN:	5320-01-490-6234



P/N MS20427M3-18 Specifications

Fastener Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.1548 Inches Minimum And 0.1900 Inches Maximum
End Item Identification:	F-22
Grip Length:	0.985 Inches Nominal
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Part Name Assigned By Controlling Agency:	Rivet
Special Features:	Shear Strength 49,000 Psi To 59,000 Psi
Material:	Nickel Alloy R-405 Overall Or Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Annealed Fed Spec Single Material Response Overall

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M3-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.