

# P/N MS20427M4-11

### **Description**

Fastener Length: 3/4", roughly 330 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS20427M411

Minimum Qty (MOQ): 200

NSN: 5320-00-226-0208

Schedule B: 7508.90.5000

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20427M4-11 Specifications

Fastener Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.200 Inches Minimum And 0.236 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy 400 Overall Or Nickel Alloy R-405 Overall
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Overall

# **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20427M4-11">https://military-fasteners.com/rivets/solid+rivets/MS20427M4-11</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.