

Description

length: 1/4", diameter: 1/8", countersunk head, monel, MS20427 series rivet, roughly 845 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS20427M44 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-118-2005 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N MS20427M4-4 Specifications

| | |
|-----------------------------|--|
| Fastener Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.201 Inches Minimum And 0.236 Inches Maximum |
| Grip Length: | 0.063 Inches Nominal |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Material: | Nickel Alloy 400 Overall Or Nickel Alloy R-405 Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M4-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.