

**Description**

length: 7/16", diameter: 1/8", countersunk head, monel, MS20427 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20427M47
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-256-1945
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS20427M4-7 Specifications

<b>Fastener Length:</b>	0.428 Inches Minimum And 0.448 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.201 Inches Minimum And 0.206 Inches Maximum
<b>Grip Length:</b>	0.251 Inches Nominal
<b>Shear Strength:</b>	49000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Nickel Alloy 400 Overall Or Nickel Alloy R-405 Overall
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M4-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.