

Description


Fastener Length: 3/8", roughly 590 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS20427M4C6 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-043-1985 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N MS20427M4C6 Specifications

| | |
|-----------------------------|--|
| Fastener Length: | 0.375 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Head Height: | 0.048 Inches Nominal |
| Shank Diameter: | 0.125 Inches Nominal |
| Shank Style: | Straight |
| Head Major Diameter: | 0.201 Inches Minimum And 0.236 Inches Maximum |
| Shear Strength: | 23000 Double Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Copper Alloy Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M4C6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.