

**Description**

Fastener Length: 3/8", roughly 590 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20427M4C6
Minimum Qty (MOQ):	100
NSN:	5320-00-043-1985
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE  
AVAILABLE

## P/N MS20427M4C6 Specifications

<b>Fastener Length:</b>	0.375 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Head Height:</b>	0.048 Inches Nominal
<b>Shank Diameter:</b>	0.125 Inches Nominal
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.201 Inches Minimum And 0.236 Inches Maximum
<b>Shear Strength:</b>	23000 Double Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Copper Alloy Overall
<b>Surface Treatment:</b>	Cadmium Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M4C6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.