

Description

Fastener Length: 3/8", roughly 590 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20427M4C6
Minimum Qty (MOQ):	100
NSN:	5320-00-043-1985
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

P/N MS20427M4C6 Specifications

Fastener Length:	0.375 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Head Height:	0.048 Inches Nominal
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.201 Inches Minimum And 0.236 Inches Maximum
Shear Strength:	23000 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Copper Alloy Overall
Surface Treatment:	Cadmium Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M4C6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.